



FEATURE OF THE PRODUCT

- Rotatable according to demand, multi-angle lamp
- Steam lined appearance, high-purity aluminum is used with excellent heat dispensation
- Constant current drive, safe, reliable, low power consumption, long service life
- Highlight integrated LED light source modules, high brightness, light is small
- Class alternative to traditional HID lamps

APPLICATIONS:

- Suitable for squares, billboards, building facades, drive-ways, parking areas and other landscape lighting places.

LED BACKPACK FLOOD LIGHT
FLOOD LIGHT



Model	DR-CQ-FLA10W	DR-CQ-FLA20W	DR-CQ-FLA30W	DR-CQ-FLA50W	DR-CQ-FLA70W	DR-CQ-FLA-100W	DR-CQ-FLA150W	DR-CQ-FLA-300W
LED Power	10W	20W	30W	50W	70W	100W	150W	300W
Size (mm)	L184xW16 5xH55	L184xW1 66xH55	L293xW24 0XH82	L385xW3 20xH106	L422xW3 20xH106	L422xW32 0xH128	L422xW38 0xH128	L422xW380x H128
Voltage	AC85- 265V	AC85- 265V	AC85- 265V	AC85- 265V	AC85- 265V	AC85- 265V	AC85- 265V	AC85-265V
Efficacy	90Lm/W	90Lm/W	90Lm/W	90Lm/W	90Lm/W	90Lm/W	90Lm/W	90Lm/W
CCT	2700- 7000K	2700- 7000K	2700- 7000K	2700- 7000K	2700- 7000K	2700- 7000K	2700- 7000K	2700-7000K
Beam Angle	120	120	120	120	120	120	120	120

WWW.ERGOFLEX426.CO.ZA - INFO@ERGOFLEX426.CO.ZA

CAPE TOWN - JOHANNESBURG - PORT ELIZABETH

LED 12V FLOOD LIGHT

FLOOD LIGHT



Model	DR-CQ-FLS10W	DR-CQ-FLS20W	DR-CQ-FLS30W	DR-CQ-FLS50W
LED Power	10W	20W	30W	50W
Size (mm)	L83xW112xH40	L140xW180xH37	L183xW223xH43	L233xW285xH47
Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V
Efficacy	90Lm/W	90Lm/W	90Lm/W	90Lm/W
CCT	2700-7000K	2700-7000K	2700-7000K	2700-7000K
Beam Angle	120degrees	120degrees	120degrees	120degrees

LED SLIM FLOOD LIGHT

FLOOD LIGHT



Model	DR-CQ-FLL10W	DR-CQ-FLL20W	DR-CQ-FLL30W	DR-CQ-FLL50W	DR-CQ-FLL-100W
LED Power	10W	20W	30W	50W	100W
Size (mm)	L83xW112xH40	L140xW180xH37	L183xW223xH43	L233xW285xH47	L285xW365xH65
Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V	AC85-265V
Efficacy	90Lm/W	90Lm/W	90Lm/W	90Lm/W	90Lm/W
CCT	2700-7000K	2700-7000K	2700-7000K	2700-7000K	2700-7000K
Beam Angle	120degrees	120degrees	120degrees	120degrees	120degrees

LED COLOR FLOOD LIGHT

FLOOD LIGHT

MULTI-ANGLE COMPREHENSIVE DISPLAY TRUE QUALITY WITHOUT MODIFICATION



BLOOMING RED



FASHION BLUE



FRESH GREEN



WARM WHITE



BEAUTIFUL WHITE

Model	DR-CQ-FLO10W	DR-CQ-FLO20W	DR-CQ-FLO30W
LED Power	10W	20W	30W
Size (mm)	L184xW165xH55	L184xW166xH55	L293xW240xH82
Voltage	AC85-265V	AC85-265V	AC85-265V
Efficacy	70-80Lm/W	70-80Lm/W	70-80Lm/W
CCT	2700-7000K	2700-7000K	2700-7000K
Beam Angle	120degrees	120degrees	120degrees
IP Grade	IP65	IP65	IP65
Ambient Temperature	-40°C to +50°C	-40°C to +50°C	-40°C to +50°C

LED TUNNEL LIGHT

TUNNEL LIGHT



Model	DR-CQ-FLT100W	DR-CQ-FLT150W	DR-CQ-FLT200W	DR-CQ-FLT250W	DR-CQ-FLT300W
LED Power	100W	150W	200W	250W	300W
Size (mm)	L380xW270xH140	L460xW320xH200	L520xW320xH210	L580xW340xH210	L690xW330xH220
Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V	AC85-265V
Efficacy	120Lm/W	120Lm/W	120Lm/W	120Lm/W	120Lm/W
CCT	2700-7000K	2700-7000K	2700-7000K	2700-7000K	2700-7000K
Beam Angle	130degrees	130degrees	130degrees	130degrees	130degrees
CRI (Ra)	Ra > 70	Ra > 70	Ra > 70	Ra > 70	Ra > 70
Power Factor	> 0.90	> 0.90	> 0.90	> 0.90	> 0.90
Life Span	>50000Hrs	> 50000Hrs	> 50000Hrs	> 50000Hrs	> 50000Hrs
IP Grade	IP66	IP66	IP66	IP66	IP66
Ambient Temperature	-40°C to +50°C	-40°C to +50°C	-40°C to +50°C	-40°C to +50°C	-40°C to +50°C