

LED T8 INTERATION

TUBE SERIES



Model	T8-0.3MTS	DR-T5S-10W	T8-0.9MTS	DR-T5S-18W	DR-T5S-24W
LED Power	6W	10W	15W	18W	24W
Size (mm)	0.3m	0.6m	0.9m	1.2m	1.5m
Voltage	AC220-240V	AC220-240V	AC220-240V	AC220-240V	AC220-240V
Efficacy	100Lm/W	100Lm/W	100Lm/W	100Lm/W	100Lm/W
CCT	2700-7000K	2700-7000K	2700-7000K	2700-7000K	2700-7000K
Beam Angle	120degrees	120degrees	120degrees	120degrees	120degrees
CRI (Ra)	Ra 70	Ra 70	Ra 70	Ra 70	Ra 70
Power Factor	0.90	0.90	0.90	0.90	0.90
Life Span	50000Hrs	50000Hrs	50000Hrs	50000Hrs	50000Hrs

LED T8 TUBE (ALUMINUM + PC)

TUBE SERIES



Model	DR-T8M/C-10W	DR-T8M/C-15W	DR-T8M/C-18W	DR-T8M/C-24W
LED Power	10W	15W	18W	24W
Size (mm)	0.6m	0.9m	1.2m	1.5m
Voltage	AC220-240V	AC220-240V	AC220-240V	AC220-240V
Efficacy	100Lm/W	100Lm/W	100Lm/W	100Lm/W
CCT	2700-7000K	2700-7000K	2700-7000K	2700-7000K
Beam Angle	120degrees	120degrees	120degrees	120degrees
CRI (Ra)	Ra 70	Ra 70	Ra 70	Ra 70
Power Factor	0.90	0.90	0.90	0.90
Life Span	50000Hrs	50000Hrs	50000Hrs	50000Hrs

LED T8 TUBE (GLASS)

TUBE SERIES



Model	DR-T8G-10W	DR-T8G-18W	DR-T8G-24W
LED Power	10W	18W	24W
Size (mm)	0.6m	1.2m	1.5m
Voltage	AC220-240V	AC220-240V	AC220-240V
Efficacy	100Lm/W	100Lm/W	100Lm/W
CCT	2700-7000K	2700-7000K	2700-7000K
Beam Angle	120degrees	120degrees	120degrees
CRI (Ra)	Ra 70	Ra 70	Ra 70
Power Factor	0.90	0.90	0.90
Life Span	50000Hrs	50000Hrs	50000Hrs

LED

TUBE FITTINGS



Model	0.6m-SLTLF	0.9m - SLTF	1.2m-SLTLF	1.5m-SLTLF	1.2 DTF	1.5 DTF	RP - 1.2m	RP - 1.5m
Model	Single Fitting	Single Fitting	Single Fitting	Single Fitting	Double Fitting	Double Fitting	Double Fitting	Double Fitting
Size (mm)	0.6m	0.9m	1.2m	1.5m	1.2m	1.5m	1.2m	1.5m
Material	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Plastic	Plastic