

SK-10W mono

| Model | SK-10W |
|--|------------------|
| Maximum Power (P _m) | 10W |
| Open Circuit Voltage(V _{oc}) | 22.2V |
| Short-Circuit Current(I _{sc}) | 0.63A |
| Maximum Power Voltage (V _{mp}) | 17.8V |
| Maximum Power Current(V _{mp}) | 0.57A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 1kg |
| Dimension | 255*350*17mm |
| Cell Technology | MONO-Si |

SK-20W mono

| Model | SK-20W |
|--|------------------|
| Maximum Power (P _m) | 20W |
| Open Circuit Voltage(V _{oc}) | 22.0V |
| Short-Circuit Current(I _{sc}) | 1.23A |
| Maximum Power Voltage (V _{mp}) | 18V |
| Maximum Power Current(V _{mp}) | 1.11A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 1.3kg |
| Dimension | 430*285*18mm |
| Cell Technology | MONO-Si |

SK-30W mono

| Model | SK-30W |
|--|------------------|
| Maximum Power (P _m) | 30W |
| Open Circuit Voltage(V _{oc}) | 22.0V |
| Short-Circuit Current(I _{sc}) | 1.84A |
| Maximum Power Voltage (V _{mp}) | 18.0V |
| Maximum Power Current(I _{mp}) | 1.66A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 2.1kg |
| Dimension | 560*350*25mm |
| Cell Technology | MONO-Si |

SK-50W mono

| Model | SK-50W |
|--|------------------|
| Maximum Power (P _m) | 50W |
| Open Circuit Voltage(V _{oc}) | 22.0V |
| Short-Circuit Current(I _{sc}) | 3.07A |
| Maximum Power Voltage (V _{mp}) | 18.0V |
| Maximum Power Current(V _{mp}) | 2.78A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 3.1kg |
| Dimension | 670*420*25mm |
| Cell Technology | MONO-Si |

SK-80W mono

| Model | SK-80W |
|--|------------------|
| Maximum Power (P _m) | 80W |
| Open Circuit Voltage(V _{oc}) | 22.0V |
| Short-Circuit Current(I _{sc}) | 4.92A |
| Maximum Power Voltage (V _{mp}) | 18.0V |
| Maximum Power Current(V _{mp}) | 4.45A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 5.2kg |
| Dimension | 780*670*30mm |
| Cell Technology | MONO-Si |

SK-100W mono

| Model | SK-100W |
|------------------------------------|------------------|
| Maximum Power (P_m) | 100W |
| Open Circuit Voltage(V_{oc}) | 22.0V |
| Short-Circuit Current(I_{sc}) | 6.14A |
| Maximum Power Voltage (V_{mp}) | 18.0V |
| Maximum Power Current(V_{mp}) | 5.56A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 7.4kg |
| Dimension | 1020*670*30mm |
| Cell Technology | MONO-Si |

SK-120W mono

| Model | SK-120W |
|--|------------------|
| Maximum Power (P _m) | 120W |
| Open Circuit Voltage(V _{oc}) | 22.0V |
| Short-Circuit Current(I _{sc}) | 7.37A |
| Maximum Power Voltage (V _{mp}) | 18.0V |
| Maximum Power Current(V _{mp}) | 6.67A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 7.8kg |
| Dimension | 1120*670*35mm |
| Cell Technology | MONO-Si |

SK-150W mono

| Model | SK-150W |
|------------------------------------|------------------|
| Maximum Power (P_m) | 150W |
| Open Circuit Voltage(V_{oc}) | 22.0V |
| Short-Circuit Current(I_{sc}) | 9.21A |
| Maximum Power Voltage (V_{mp}) | 18.0V |
| Maximum Power Current(I_{mp}) | 8.33A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 11kg |
| Dimension | 1480*670*35mm |
| Cell Technology | MONO-Si |

SK-200W mono

| Model | SK-200W |
|--|------------------|
| Maximum Power (P _m) | 200W |
| Open Circuit Voltage(V _{oc}) | 45.2V |
| Short-Circuit Current(I _{sc}) | 5.72A |
| Maximum Power Voltage (V _{mp}) | 36.9V |
| Maximum Power Current(V _{mp}) | 5.43A |
| Power Tolerance | 0~+3% |
| Maximum System Voltage | DC1000V |
| Module Application | Class A |
| Nominal Operating Temperature | 45 ± 2 °C |
| Operating Temperature | -40 °C to +85 °C |
| Weight | 14.3kg |
| Dimension | 1320*990*35mm |
| Cell Technology | MONO-Si |



Mono-crystalline
Solar Panel

WWW.ERGOFLEX426.CO.ZA - INFO@ERGOFLEX426.CO.ZA

CAPE TOWN - JOHANNESBURG - PORT ELIZABETH